

DESCRIPTION

Doxa Fully Synthetic Diesel Engine Oil is a high performance diesel engine oil designed to meet the most severe performance requirements of the latest high output, low emission European and American diesel engines. It is formulated with premium quality base oil and superior additive technology to provide the highest diesel engine performance levels.

APPLICATION

- Naturally aspirated and turbocharged high speed, four-stroke diesel engines.
- All automotive diesel engines.
- High speed diesel engines
- Commercial road transport in light, medium and heavy-duty service.
- On and Off-highway vehicles.
- All construction and earthmoving equipment.
- Stop & Go vehicles in high soot loading services.

BENEFITS

- Extra Soot dispersancy keeps fuel soot in suspension; avoid filter plugging, oil thickening and abrasive polishing wear.
- Exceptional oxidation stability at high temperature, and soot control minimizes degradation sludge formation and oil thickening, consequently longer drain intervals.
- Multipurpose oil for old and new engines.
- Foam protection
- Shear-stable viscosity Index improver prevents oil flow through the piston rings by maintaining oil viscosity in the high temperature ring
- Corrosion and rust inhibition

PERFORMANCE LEVEL

API CK 4, CJ 4, CI 4 PLUS and all prior categories.

PRODUCT CHARACTERISTICS

METHOD	TEST	RESULT	UNITS
SAE GRADE		10W30	
ASTM D-1298	Specific Gravity	0.85 - 0.86	gm/ml
ASTM D-445	Kinematic Viscosity @ 104°F / 40°C	60 - 80	mm²/s
ASTM D-445	Kinematic Viscosity @ 212°F / 100°C	9.3 - 12.4	mm²/s
ASTM D-2270	Viscosity Index	min 160	-
ASTM D-92	Corrected Flash Point	236	°C
ASTM D-97	Pour Point	-36	°C
ASTM D-2896	Total Base Number	min 10	mg KOH/g